


# SlimPOS

The one that creates a new trend



## SlimPOS is

15" touch screen POS system equipped with Intel Celeron M 1.5GHz processor. It supports diversified applications with the choice of MSR, 12" 2nd display or VFD customer display. Also, its various ports including two front USB ports, make the model compatible with numerous devices. Its stylish and slim design fits very well into any limited counter space in retail, restaurant and hospitality sector. The robust structure with aluminum die cast base features makes it capable to withstand daily usage under harsh operating environments.



**1. Flexible angle adjustment  
to provide optimal visual comfort**

Swivel : 0 ~180  
Tilt : 0 - 80

**3. Dual monitor**


12" 2nd LCD monitor  
1024 x 768 Resolution

**2. Customer display**

VFD or LCD type  
20 space columns x 2 lines

**4. Magnetic Stripe Reader (MSR)  
Smart Card Reader (SCR)**

# What's Special



**High Serviceability** Considerate mechanical design for easy HDD maintenance. You need to release only one screw to reach HDD.

**Innovative Free-Noise** Cooling Design

**Touch Screen** with Flexible To Adjusting Angle  
(4 Sides – Up & Down, Left & Right)



**Space Saving** footprint



**Easy access** Front USB design allows easy access of various devices.

# System

CPU(Support)		Intel Celeron Mobile 1.5GHz
Chipset		Intel 915GME/910GML
HDD		SATA 2.5inch (Default 160GB)
Memory		DDR2 SODIMM x 1 slot (Default 1GB up to 2GB)
VGA		Intel 82915GM GMCH (Independent dual display)
Display		15" TFT LCD with 5-wired resistive Touch Screen 1024 x 768 resolution
Internal I/O	USB	2 Ports (reserved for Touch controller & SCR EMV card)
	PS/2	1 Keyboard reserved for MSR controller
	RS-232	COM 4 reserved for VFD or 2nd display / COM 5 & 6 with 9 pin header
	D-SUB	Reserved for 2nd display
	Extension	MINI PCI
	LVDS	Main display use
External I/O	Parallel	1 Port
	USB	Front 2, Rear 2
	PS/2	Mouse 1 / Keyboard 1
	RS-232	COM 1 ~ 3 with +5/12V power output on 9pin
	LAN	GbE LAN
	Audio	Each 1 Line-out/ Line-in/ Mic
Options	MSR	Comply with ISO 7811, Support 1 & 2, 2 & 3, 1& 2 & 3 track
	SCR	EMV level
	Dallas	Dallas I-button reader
	VFD	VFD type customer display (20 x 2)
	2nd LCD	12.1" LCD : 1024 x 768 resolution
	DVR	DVR Card : 4 channels support
	WiFi	Mini PCI for wireless LAN
VGA	Mini PCI for VGA card	
Qualification		CE, FCC, KCC
Power Supply		AC 110 or 220V (Max.240 watt)
OS Support		Linux, Windows 2000/XP/XPE, WEPOS, POS Ready, Windows 7

\* Specifications are subject to change without prior notice



**POSBANK**® Co.,Ltd.

Room 805~808 New T Castle B/D, 429-1 Gasan-Dong, Geumcheon-Gu Seoul, Korea

Tel. +82-2-2626-9118 Fax. +82-2-2626-9119 E-MAIL Sales@posbank.com

www.posbank.com

Copyright(c) POSBANK Co.,Ltd. All rights reserved.